

## ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

www.sodeca.com

|               |  |   |   |                          |
|---------------|--|---|---|--------------------------|
| b) Model      | f) Thermal efficiency of heat recovery (%) | j) Face velocity at design flow rate                    | n) Static efficiency of fans according to (EU) 327/2011 | q) Visual filter warning |
| c) Typology   | g) Nominal flowrate                        | k) Nominal external pressure                            | o1) Max. internal leakage rate                          | r) LWA radiated          |
| d) Drive type | h) Effective electric power input          | l) Internal pressure drop of ventilation components     | o2) Max. external leakage rate                          |                          |
| e) HRS type   | i) SFPint                                  | m) Internal pressure drop of non-ventilation components | p) Energy performance of the filters                    |                          |

| b)                   | c)         | d)             | e)   | f) | g)    | h)    | i)     | j)   | k)  | l) | m) | n)   | o1) | o2) | p)    | q)         | r)  | ERP  |
|----------------------|------------|----------------|------|----|-------|-------|--------|------|-----|----|----|------|-----|-----|-------|------------|-----|------|
|                      |            |                |      | %  | m³/s  | kW    | W/m³/s | m/s  | Pa  | Pa | Pa | %    | %   | %   |       |            | dBA |      |
| CJBD/F-1919-4M 1/5   | NRVU / UVU | Variable speed | None |    | 0.279 | 0.192 | 230    | 1.80 | 198 | 35 |    | 33.2 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-2525-4M 1/2   | NRVU / UVU | Variable speed | None |    | 0.546 | 0.419 | 230    | 2.80 | 286 | 54 |    | 40.7 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-2525-4M 3/4   | NRVU / UVU | Variable speed | None |    | 0.555 | 0.433 | 230    | 2.90 | 269 | 55 |    | 40.2 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-2525-6M 1/5   | NRVU / UVU | Variable speed | None |    | 0.445 | 0.175 | 230    | 2.30 | 81  | 44 |    | 34.1 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-2525-6M 1/3   | NRVU / UVU | Variable speed | None |    | 0.462 | 0.195 | 230    | 2.40 | 90  | 46 |    | 34.2 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-2828-4M 1/2   | NRVU / UVU | Variable speed | None |    | 0.692 | 0.613 | 230    | 2.90 | 393 | 55 |    | 44.5 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-2828-4M 3/4   | NRVU / UVU | Variable speed | None |    | 0.666 | 0.610 | 230    | 2.80 | 413 | 53 |    | 40.9 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-2828-6M 1/3   | NRVU / UVU | Variable speed | None |    | 0.581 | 0.273 | 230    | 2.40 | 157 | 46 |    | 38.7 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-3333-6T 1 1/2 | NRVU / UVU | Variable speed | None |    | 0.867 | 0.601 | 230    | 2.60 | 270 | 49 |    | 42.9 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-3333-6M 3/4   | NRVU / UVU | Variable speed | None |    | 0.822 | 0.577 | 230    | 2.50 | 268 | 47 |    | 45.9 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-3333-6M 1     | NRVU / UVU | Variable speed | None |    | 0.849 | 0.591 | 230    | 2.50 | 256 | 49 |    | 42.2 |     | 2.6 | G4: G | See manual |     | 2018 |
| CJBD/F-3939-6T 3     | NRVU / UVU | Variable speed | None |    | 1.476 | 1.413 | 230    | 3.20 | 362 | 61 |    | 44.2 |     | 2.6 | G4: G | See manual |     | 2018 |