

ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

a) Brand	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU
b) Model	CA/LINE-10	CA/LINE-12	CA/LINE-15	CA/LINE-16	CA/LINE-20	CA/LINE-25
c) Specific energy consumption (SEC) average climate (kWh/(m².yr))	-23.7	-24.2	-24.8	-25	-24	-24.1
c) Specific energy consumption (SEC) cold climate (kWh/(m².yr))	-50.8	-51.2	-51.8	-52.1	-51	-51.2
c) Specific energy consumption (SEC) warm climate (kWh/(m².yr))	-8.2	-8.7	-9.3	-9.5	-8.5	-8.6
c) SEC class	C	C	C	C	C	C
d) Typology	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU
e) Drive type	Flerhastighet	Flerhastighet	Flerhastighet	Flerhastighet	Flerhastighet	Flerhastighet
f) HRS type	Ingen	Ingen	Ingen	Ingen	Ingen	Ingen
g) Thermal efficiency of heat recovery (%)						
h) Maximum flow rate (m³/h)	210	259	381	408	857	922
i) Electric power input of the fan drive at maximum flow rate (W)	41	46	58	57	158	164
j) Sound power level (LWA) (dBA)	61	63	63	63	69	69
k) Reference flow rate (m³/s)	0.041	0.05	0.074	0.079	0.167	0.179
l) Reference pressure difference (Pa)	208	198	210	226	295	295
m) SPI (W/m³/h)	0.28	0.25	0.22	0.2	0.26	0.26
n) Control factor	0.65	0.65	0.65	0.65	0.65	0.65
n) Control typology	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll
o) Declared max. internal leakage rate (%)	2.0	2.0	2.0	2.0	2.0	2.0
o) Max. external leakage rate (%)	3.2	2.7	1.8	1.7	0.8	0.7
p) Mixing rate	0.00	0.00	0.00	0.00	0.00	0.00
q) Position and description of visual filter warning	Ikke aktuelt	Ikke aktuelt	Ikke aktuelt	Ikke aktuelt	Ikke aktuelt	Ikke aktuelt
r) Instructions to install regulated grilles	Se manual	Se manual	Se manual	Se manual	Se manual	Se manual
s) Website	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com
t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa	0.00	0.00	0.00	0.00	0.00	0.00
u) Indoor/outdoor air tightness	0.00	0.00	0.00	0.00	0.00	0.00
v) Annual electricity consumption (AEC) average climate (kWh/yr)	200	200	100	100	200	200
v) Annual electricity consumption (AEC) warm climate (kWh/yr)	200	200	100	100	200	200
v) Annual electricity consumption (AEC) cold climate (kWh/yr)	200	200	100	100	200	200
w) Annual heating saved (AHS) average climate (kWh/yr)	2800	2800	2800	2800	2800	2800
w) Annual heating saved (AHS) warm climate (kWh/yr)	1300	1300	1300	1300	1300	1300
w) Annual heating saved (AHS) cold climate (kWh/yr)	5500	5500	5500	5500	5500	5500
ErP compliance	2018	2018	2018	2018	2018	2018